

PERFORMANCE		Winding codes	3VDN	3VHS
		UNIT	FREE AIR CONVECTION	FREE AIR CONVECTION
Tp	Peak torque	Nm	3320	3320
Tc	Continuous torque	Nm	705	705
Ts	Stall torque	Nm	538	538
Kt	Torque constant	Nm/Arms	40.3	20.1
Ku	Back EMF constant (*)	Vrms/(rad/s)	23.3	11.7
Km	Motor constant	Nm/√W	27.2	27.2
R20	Electrical resistance at 20°C (*)	Ohm	1.46	0.364
L1	Electrical inductance (*)	mH	19.3	4.81
Ip	Peak current	Arms	159	318
Ic	Continuous current	Arms	17.8	35.5
Is	Stall current	Arms	13.5	26.9
Pc	Max. continuous power dissipation	W	986	986

SPECIFICATIONS		UNIT		
Udc	Nominal input voltage	VDC	600	600
τth	Thermal time constant	s	3220	3220
Rth	Thermal resistance	K/W	0.112	0.112
2p	Number of poles	-	88	88
J	Rotor inertia	kg.m ²	0.921	0.921
Mr	Rotor mass	kg	19.2	19.2
Ms	Stator mass	kg	44.0	44.0
Td	Max. detent torque (average to peak)	Nm	28	28
ns	Stall speed	rpm	0.0042	0.0042

Notes: (*) terminal to terminal.

Hypothesis and tolerances are in ETEL's Handbook.

Ambient temperature = 20 °C. Max. coil temperature = 130 °C.

Stator connected to a total surface of 0.50 m² and rotor to a total surface of 0.320 m²

Caution: Any use of the motor beyond speed/force limit could lead to hazardous voltage and serious injuries. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the motor is used in an improper way.

